

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A

INSTALLATION INSTRUCTIONS MODEL GBA-xx GRAB BAR

1. Select the mounting location for the Grab Bar and assure that the mounting location is relatively flat and structurally sound for installation.
2. Drill two 7/16" diameter holes 7-1/8" apart for mounting.
3. Apply a bead of silicone to one side of each washer and install the washer and bolts to the Grab Bar from the back side of the tub. Using a 9/16" wrench or socket tighten the bolts to 20 ft-lb maximum.



P/N 900111 Rev A